

 **First in Quality. Built to Last.**



BUNDLING TUNNELS PERFORMANCE SERIES

RELIABLE SHRINK PERFORMANCE

EASTEY'S ETB Series bundling tunnels offer the reliability needed to provide positive shrinking and are designed specifically for bundling applications.

MODELS

ETB3012, ETB3020

BUILT RIGHT...PRICED RIGHT


Proven reliable over and over again, these EASTEY bundling tunnels provide you with all the quality features found in much higher priced machines. They are designed and built to give you all the features needed for positive shrinking of polyethylene film.

RUGGED DESIGN

EASTEY'S top of the line bundling tunnels are expertly welded on 12 gauge steel frames and designed to handle the day to day abuse of most bundling applications. Each tunnel utilizes four-directional variable air flow to provide a positive shrink. See for yourself why EASTEY has been a leader in the shrink packaging industry for over 25 years.

STANDARD FEATURES

- Designed to seal polyethylene film
- All-welded main frame from 12 gauge steel
- 39" chamber length to ensure proper shrinking of film
- Dead roller conveyor
- Sealed bearings (not bushings) on drive and idler shafts
- Adjustable solid state temperature control for a variety of films
- Four-directional air flow provides positive shrinking
- Variable air flow and air velocity for a variety of products and applications
- Large ducting creates more air volume inside tunnel
- Optional side plates (top and sides) for air flow patterning and quick changeover for different products
- Delayed cool down and over temperature protection
- Heavy duty casters for transportation within plant
- Leveling legs provide sturdy base once in place
- Custom two part epoxy finish resists scratching
- Available in 220v - single or 3-phase
- Easy to use design requires minimal training, maintenance, and trouble free operation
- Made in the USA



1. **Reliable Shrink Performance**
Proven Eastey tunnels provide positive shrinking of polyethylene film
2. **Dead Roller**
Designed specifically for polyethylene films
3. **Control Panel**
Easy to use control panel lets users adjust for their specific application
4. **Inside of Tunnel**
Four directional air flow provides positive shrinking

MODEL NUMBER	MACHINE DIMENSIONS			CHAMBER DIMENSIONS			CONVEYOR LENGTH	STANDARD POWER			WEIGHT	SHP WT.
	WIDTH	HEIGHT	LENGTH	WIDTH	HEIGHT	LENGTH		VOLTS	AMPS	PHASE		
ETB3012	45"	67"	59"	30"	12"	39"	59"	220	25/50	1/3	1200 lbs	1300 lbs
	114 cm	170 cm	149 cm	76 cm	30 cm	149 cm					546 kg	591 kg
ETB3020	45"	75"	59"	30"	20"	39"	59"	220	25/50	1/3	1250 lbs	1350 lbs
	114 cm	190 cm	149 cm	76 cm	50 cm	149 cm					569 kg	612 kg



7041 Boone Avenue North, Brooklyn Park, MN 55428
 (763) 428-4846 1 (800) 835-9344
 www.eastey.com info@eastey.com

